

# System Unit HW-227, HFC-227ea Engineered Extinguishing Units, 609 psig (42 bar) HW-227

File Number: EX15697

**COMPANY**

**HONEYWELL MIDDLE EAST FZE**

PO Box 18530  
DUBAI, United Arab Emirates

**SYSTEM UNIT INFO**

HW-227, HFC-227ea Engineered Extinguishing Units, 609 psig (42 bar) HW-227 Honeywell HFC-227ea Engineered Extinguishing System Units.  
Engineered, Halocarbon

CLEAN AGENT EXTINGUISHING SYSTEM UNITS	VALUE
Extinguishing Agent (ASHRAE Designation)	HFC-227ea

MANUALS AND BULLETINS		
Part No.	Description	Date/Rev
HSN-MNL-H1-R0	Design, Installation, Operation Maintenance and Refilling Manual	19/Feb/2025/R0

SYSTEM UNIT INFORMATION		
Operating Pressure at Temperature	Minimum Operating Temperature	Maximum Operating Temperature
609 psig (42 bar) @ 70°F (21°C)	0 C (32 F)	50 C (122 F)

**THESE INSTALLATIONS REQUIRE THE USE OF THE LISTEE'S FLOW CALCULATION SOFTWARE:**

---

**Software Name/Version**

---

HSN-HF-SW-02

---

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."