



System Unit HW-5112, FK-5-1-12 Engineered Extinguishing Units, 609 psig (42 bar)

File Number: EX15697

COMPANY

HONEYWELL MIDDLE EAST FZE

PO Box 18530

DUBAI, United Arab Emirates

SYSTEM UNIT INFO

HW-5112, FK-5-1-12 Engineered Extinguishing Units, 609 psig (42 bar) HW-5112

Engineered, Halocarbon

CLEAN AGENT EXTINGUISHING SYSTEM UNITS	VALUE
Extinguishing Agent (ASHRAE Designation)	FK-5-1-12

MANUALS AND BULLETINS		
Part No.	Description	Date/Rev
HSN-MNL-F1-R0	Design, Installation, Operation Maintenance and Refilling Manual	October 2024/ Rev. 0

SYSTEM UNIT INFORMATION		
Operating Pressure at Temperature	Minimum Operating Temperature	Maximum Operating Temperature
609 psig (42 bar)	4.4 C (40 F)	50 C (122 F)

THESE INSTALLATIONS REQUIRE THE USE OF THE LISTEE'S FLOW CALCULATION SOFTWARE:
Software Name/Version
Honeywell FK-5-1-12 Flow Calculation Software Version 7.8.0, part number HSN-FK-SW-02

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."